

How to install your new smoke alarm

Installing the Brooks smoke detector, flashing strobe light and vibration pad (EiB650iRF and EiB170RFAU).

Smoke detector

1. Decide where to put the smoke detector

It is important to know that enough smoke has to enter the smoke detector for it to alert you of a fire. Your smoke detector works best when it is no further than 7.5 metres from these areas and where air circulates well, away from corners and recesses. This is because you cannot smell smoke from a fire when you are sleeping.

In Queensland, smoke alarms must be installed on each storey:

- a. in each bedroom; and
- b. in hallways which connect bedrooms and the rest of the dwelling; or if there is no hallway, between the bedrooms and other parts of the storey;

If there are no bedrooms on a storey at least one smoke alarm must be installed in the most likely path of travel to exit the dwelling.

2. Remove the base plate by twisting it in an anti-clockwise direction.
3. Hold the base plate against the ceiling and mark where you need to drill the holes.
4. Drill two holes.
5. Then use the two screws included to attach the base plate to your ceiling.

Please refer to current state legislation to obtain mandatory smoke alarm requirements.

Flashing strobe light and vibration pad

1. Place the flashing strobe light on the bedside table, and the vibration pad under the pillow on the bed.
2. Plug the flashing strobe light (with the connected vibration pad) into a power point (normally at the bedside table). You will see a green light on flashing strobe light.

Testing

1. Attach the smoke alarm to the base.
2. Twist the smoke alarm onto the base in a clockwise direction to activate the alarm. It will automatically and wirelessly connect with the flashing strobe light and vibration pad.
3. Press the "test" button on your flashing strobe light. It will flash and the vibrating pad will vibrate.



Maintenance

To make sure the alarm is working properly you should do two things **every month**:

- Vacuum around the vents on the detector on your ceiling
- Press the "test" button on the flashing strobe light

There is no need to change battery in the smoke alarm as it is a 10-year lithium battery. Remember to keep flashing strobe light plugged in (the back-up battery lasts approximately one week). As this is a wireless system, the smoke detector, flashing strobe light and vibration pad can be taken with you if you move house.

Additional items

You can purchase additional smoke detectors, flashing strobe lights, vibration pads and other items from our eShop <https://shop.hearspace.org/>

If you have any questions, please contact Deaf Connect via phone, (07) 3892 8500 or email smoke.alarms@deafconnect.org.au



Instructions created by Deaf Connect and Brooks Australia.

2/49 Boyland Avenue, Coopers Plains QLD 4108

P.O. Box 511 Archerfield QLD 4108

P: (07) 3373 8222

F: (07) 3373 8022